

UHA-60196

Harrier 2 Ingrade

LIGMAN
NORTH AMERICA

Construction

Aluminum

Less than 0.1% copper content - Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength, clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

Surge Suppression

Standard 10kv surge suppressor provided with all fixtures.

BUG Rating

B0 - U3 - G0

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

MicroPRIM Finishes

MicroPRIM is Ligman's trade marked decorative powder coating technology that permanently infuses colors, patterns, or imagery directly into the surface of luminaires and poles while providing protections that standard powder coating does not offer.

MicroPRIM finishes include nature-inspired wood grains and stone aesthetics, material-inspired finishes such as brushed metal, concrete, and carbon fiber. Solid colors in Ligman standard colors, as well as any RAL or Pantone color. Decorative patterns, custom imagery and more.

Coating and Infusion Process

Metal components are pre-treated and powder coated with a proprietary polyurethane-based coating engineered for outdoor architectural use. Decorative patterns or imagery are then permanently infused into the cured powder coat through a heat-based process, creating a durable, integrated finish.

Performance and Validation

MicroPRIM finishes are suitable for indoor and outdoor applications and meet AAMA 2605 architectural coating requirements. Performance is validated through laboratory and real-world testing to ASTM standards for UV exposure, adhesion, abrasion, impact, salt spray, chemical resistance, and graffiti resistance.

All MicroPRIM finishes are backed by Ligman's 10-year warranty.

Key Performance Attributes

- Anti-graffiti resistance
- UV and weather resistance
- Scratch and abrasion resistance
- Natatorium Rated for installation in corrosive environments)

Hardware

Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Optics & LED



Precise optic design provides exceptional light control and precise distribution of light.
LED CRI > 80

Lumen - Maintenance Life

L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)



6w LED 291 Lumens
IP67 • Suitable For Wet Locations
IK10 • Impact Resistant (Vandal Resistant)
Weight 1.1 lbs (A) 1.5 lbs (S)



Complete, flexible, competitive accent and floodlight ingrounds. The lighting industry's leading quality low-cost inground fixture family.

A top range of inground uplights with a choice of round or square stainless steel or painted aluminum front rings. This 4.7" inground luminaire is suitable as a marker light for illuminating shopping and pedestrian areas, parks, gardens and sculptures. This low glare luminaire is provided with a 0.4" thick tempered glass and is rated as a walkover luminaire. The glass has a special wrap around high temperature silicone gasket that provides additional ingress protection.

To ensure efficient drainage, gravel must be used to a depth of 17" beneath the housing, and should also be placed around the luminaire. Low copper content die-cast aluminum housing with high corrosion resistance. The 0.24" thick front ring is available in grade 316 stainless steel or aluminum.


Stainless steel fasteners in grade 316. Standard recessing box in high density polyethylene.

NOTE: This luminaire is provided with an integral driver, however a remote mounted driver, as well as a waterproof remote driver box can be specified as an option.


Additional Options (Consult Factory For Pricing)



A80191
3" x 10" Remote Enclosure Box



F
Frosted Lens (78° Beam)



UHA-60196

Harrier 2 Ingrade

PROJECT					DATE	
QUANTITY		TYPE		NOTE		

ORDERING EXAMPLE || UHA - 60196 - 6w - S - W30 - 120/277v

UHA-60196					
	LAMP	FRAME	LED COLOR	FINISH COLOR	VOLTAGE
	6w LED 291 Lumens	A - Aluminum - CHOOSE FINISH COLOR S - Stainless Steel NO FINISH COLOR	W27 - 2700K W30 - 3000K W35 - 3500K W40 - 4000K	01 - BLACK RAL 9011 02 - DARK GREY RAL 7043 03 - WHITE RAL 9003 04 - METALLIC SILVER RAL 9006 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL	120/277v

--	--	--

ADDITIONAL OPTIONS

- F - Frosted Lens (78° Beam)
- NAT - Natatorium Rated
- A80191 - 3"x10" Remote Box

More Custom Finishes Available Upon Request

Consult factory for pricing and lead times

MicroPRIM FINISHES

- | | |
|--|-----------------------------|
|  | SW01 - OAK FINISH |
|  | SW02 - WALNUT FINISH |
|  | SW03 - PINE FINISH |
|  | DF - DOUGLAS FIR FINISH |
|  | CW - CHERRY WOOD FINISH |
|  | NW - NATIONAL WALNUT FINISH |
|  | SU01 - CONCRETE FINISH |
|  | SU02 - SOFTSCAPE FINISH |
|  | SU03 - STONE FINISH |
|  | SU04 - CORTEN FINISH |
|  | CSM - Custom Image/Pattern |

MicroPRIM FINISHES

- | | |
|---|------------------------------|
|  | MP - MAPLE FINISH |
|  | MHG - MAHOGANY FINISH |
|  | BH - BEECH FINISH |
|  | CN - CHESTNUT FINISH |
|  | WMBL - WHITE MARBLE FINISH |
|  | MBL - MARBLE FINISH |
|  | GRNT - GRANITE FINISH |
|  | BGD - BRUSHED GOLD FINISH |
|  | BBRZ - BRUSHED BRONZE FINISH |
|  | CAMO - CAMOUFLAGE FINISH |

- | | |
|---|---|
|  | MP01 - MicroPRIM RAL 9011 Black (Glossy) |
|  | MP02 - MicroPRIM RAL 7043 Dark Grey (Glossy) |
|  | MP03 - MicroPRIM RAL 9003 White (Glossy) |
|  | MP04 - MicroPRIM RAL 9006 Metallic Silver (Glossy) |
|  | MP05 - MicroPRIM RAL 9006 Matte Silver (Matte/Textured) |
|  | MP06 - MicroPRIM Ligman Bronze (Glossy) |
|  | MP07 - MicroPRIM Custom Color (Glossy) |



MicroPRIM Finish