

UVK-10012

Vekter 4 Double Head Bollard

microVos
TECHNOLOGY

LIGMAN
NORTH AMERICA



Construction

Aluminum

Less than 0.1% copper content - Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength, clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

Surge Suppression

Standard 10kv surge suppressor provided with all fixtures.

BUG Rating

B2 - U0 - G0

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

Inspired by Nature Finishes

The Inspired by nature Finishing is a unique system of decorative powder coating. Our metal decoration process can easily transform the appearance of metal or aluminum product into a wood grain finish.

This patented technology enables the simulation of wood grain, and even marble or granite finish through the use of decorative powder coating.

The wood grain finish is so realistic that it's almost undistinguishable from real wood, even from a close visual inspection. The system of coating permeates the entire thickness of the coat and as a result, the coating cannot be removed by normal rubbing, chipping, or scratching.

The Coating Process

After pre-treatment the prepared parts are powder coated with a specially formulated polyurethane powder. This powder provides protection against wear, abrasion, impact and corrosion and acts as the relief base color for the finalized metal decoration.

The component is then wrapped with a sheet of non-porous film with the selected decoration pattern printed on it using special high temperature inks.

This printed film transfer is vacuum-sealed to the surface for a complete thermo print and then transferred into a customized oven. The oven transforms the ink into different forms within the paint layer before it becomes solid. Finally, the film is removed, and a vivid timber look on aluminum remains.

Wood grain coating can create beautiful wood-looking products of any sort. There are over 300 combinations of designs currently in use. Wood grains can be made with different colors, designs, etc.

Our powder coatings are certified for indoor and outdoor applications and are backed by a comprehensive warranty. These coatings rise to the highest conceivable standard of performance excellence and design innovation.

Added Benefits

- Resistance to salt-acid room, accelerated aging
- Boiling water, lime and condensed water resistant
- Anti-Graffiti, Anti-Slip, Anti-Microbial, Anti-Scratch
- Super durable (UV resistant)
- TGIC free (non-toxic)

Hardware

Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Optics & LED

Precise optic design provides exceptional light control and precise distribution of light.
LED CRI > 80

Lumen - Maintenance Life

L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Flexible bollard pathway and wayfinding luminaires. Sleek, angular, technical and powerful professional lighting solutions.

The Vekter bollard range is designed utilizing specially developed optics to provide exceptional spacing and uniformity. This fixture complements the Vekter wall and pole top luminaire.


This light fixture is available in 21w and 30w configurations with a single or double head options with a selection of beam spreads that include Type II, III, IV and type V in medium, wide, very wide and extra wide distributions.

This fixture range is unique in that designer's can be creative with the required light distribution and incorporate various optics within the same fixture. e.g using type II and type IV distribution optics within the same fixture. Developed for lighting driveways, pathways and squares.

To meet International Dark Sky criteria, 3000k or warmer LEDs must be selected.

Additional Options (Consult Factory For Pricing)


2x28w LED 2x3330 Lumens
IP65 • Suitable For Wet Locations
IK08 • Impact Resistant (Vandal Resistant)
Weight 24.6 lbs




Mounting Detail

microVos
TECHNOLOGY


Ligman's micro Variable Optical System provides the ability to interchange, mix & rotate optics to provide specific light distributions for optimized spacing and uniformity.




The variable optic system allows for the designer to create hybrid distributions for precise lighting requirements.



HYBRID
TYPE I & TYPE IV




IHSS
Integrated House Side Shield



SP
Square Pole

CITY OF FLAGSTAFF & TURTLE FRIENDLY COMPLIANT



Narrow-Spectrum Amber LEDs

Peak wavelength between 585 & 595 nanometers and a full width of 50% power no greater than 15 nanometers.

PROJECT					DATE	
QUANTITY		TYPE		NOTE		

ORDERING EXAMPLE || UVK - 10012 - 2x28w - T2 - W30 - 02 - 120/277v - Options

UVK-10012					
	LAMP	BEAM	LED COLOR	FINISH COLOR	VOLTAGE
	2x28w LED 2x3330 Lumens	T1 - Type I Distribution T2 - Type II Distribution T3 - Type III Distribution T4 - Type IV Distribution M - Medium 31" W - Wide 53" VW - Very Wide 67" EW - Extra Wide 1119" T1 T2 T3 T4	W27 - 2700K W30 - 3000K W35 - 3500K W40 - 4000K	01 - BLACK RAL 9011 02 - DARK GREY RAL 7043 03 - WHITE RAL 9003 04 - METALLIC SILVER RAL 9006 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL INSPIRED BY NATURE FINISHES SW01 - OAK FINISH SW02 - WALNUT FINISH SW03- PINE FINISH DF - DOUGLAS FIR FINISH CW - CHERRY WOOD FINISH NW - NATIONAL WALNUT FINISH SU01 - CONCRETE FINISH SU02 - SOFTSCAPE FINISH SU03 - STONE FINISH SU04 - CORTEN FINISH	120/277v Other - Specify

ADDITIONAL OPTIONS

- NAT - Natatorium Rated

DIM - 0-10v Dimming

AMB - Turtle Friendly Amber LED

SP - Square Pole
- F - Frosted Lens

HGT - Custom Bollard Height

IHSS - Integrated House Side Shield

More Custom Finishes Available Upon Request

Consult factory for pricing and lead times

Oak	Cherry	Beech	Carbon
Walnut	Chestnut	Bamboo	Galvanized
Pine	Mahogany	Birch	Steel



Vekter Product Family

				
Vekter 1 • UVK-30001-20w-2446lm • UVK-30002-28w-3330lm	Vekter 2 • UVK-30003-37w-5143lm • UVK-30004-54w-6954lm	Vekter 3 • UVK-10001-20w-2473lm • UVK-10002-28w-3330lm	Vekter 4 • UVK-10011-2x20w-2x2473lm • UVK-10012-2x28w-2x3330lm	Vekter 5 • UVK-90001-37w-5143lm • UVK-90002-54w-6954lm
				
Vekter 6 • UVK-90011-2x37w-2x5143lm • UVK-90012-2x54w-2x6954lm	Vekter 7 • UVK-30011-20w-2473lm • UVK-30012-28w-3330lm	Vekter 8 • UVK-30031-37w-5143lm • UVK-30032-54w-6954lm	Vekter 9 • UVK-30021-20w-2473lm • UVK-30022-28w-3330lm	Vekter 10 • UVK-30041-37w-5143lm • UVK-30042-54w-6954lm
				
Vekter 11 - 13.1' • UVK-20001-20w-2473lm • UVK-20002-28w-3330lm	Vekter 12 - 13.1' • UVK-20003-37w-5143lm • UVK-20004-54w-6954lm	Vekter 13 - 13.1' • UVK-20011-2x20w-2x2473lm • UVK-20012-2x28w-2x3330lm	Vekter 14 - 13.1' • UVK-20013-2x37w-2x5143lm • UVK-20014-2x54w-2x6954lm	Vekter 15 • UVK-90021-4x20w-4x2473lm • UVK-90022-4x28w-4x3330lm
				
Vekter 16 • UVK-90031-4x37w-4x5143lm • UVK-90032-4x54w-4x6954lm	Vekter 17 - 19.6' • UVK-20021-20w-2473lm • UVK-20022-28w-3330lm	Vekter 18 - 19.6' • UVK-20023-37w-5143lm • UVK-20024-54w-6954lm	Vekter 19 - 19.6' • UVK-20031-2x20w-2x2473lm • UVK-20032-2x28w-2x3330lm	Vekter 20 - 19.6' • UVK-20033-2x37w-2x5143lm • UVK-20034-2x54w-2x6954lm



Vekter 25

- UVK-90041-20w-2473lm
- UVK-90042-28w-3330lm



Vekter 26

- UVK-90051-2x20w-2x2473lm
- UVK-90052-2x28w-2x3330lm



Vekter 27

- UVK-90061-37w-5143lm
- UVK-90062-54w-6954lm



Vekter 28

- UVK-90071-2x37w-2x5143lm
- UVK-90072-2x54w-2x6954lm